

AWNING WINDOW

European Design. Texas Performance.



Hinges at the top and opens outward from the bottom, providing excellent ventilation even during light rain. The thermally broken aluminum frame delivers superior energy efficiency while the compact design fits perfectly above or below other window units.

Slim 2-inch frames maximize natural light. Friction stays hold the sash at any angle, and dual EPDM compression gaskets ensure a weathertight seal when closed.

SAVE 30–50% vs. comparable US & European manufactured products — same quality, direct from factory

KEY FEATURES

- Top-hinged outward-opening operation
- Thermally broken aluminum with polyamide barrier
- Friction stay holds sash at any opening angle
- Optional retractable insect screen available
- AAMA 2604/2605 powder coat finish
- Custom sizes down to the millimeter

TECHNICAL SPECIFICATIONS

SPEC	DETAIL	SPEC	DETAIL
Frame Material	Thermally broken aluminum, polyamide barrier	Finish	Matte black powder coat, AAMA 2604/2605
Frame Profile	2" slim frames, mitered corners	Gaskets	EPDM dual weather stripping
Glass Unit	24mm double-pane IGU, Low-E, argon	Sizes	Custom sizes down to the millimeter
Operation	Top-hinged outward, friction stay	Energy	ENERGY STAR, U-factor 0.30
Locking	Multi-point espagnolette	Warranty	10-year frame, 2-year hardware

ENERGY PERFORMANCE RATINGS

0.30

U-Factor

0.23

Solar Heat Gain Coefficient

0.49

Visible Transmittance

53

Condensation Resistance