CASEMENT WINDOW

European Design. Texas Performance.

Sleek modern aesthetics meet the thermal performance demanded by Texas climate extremes. Outward-opening side-hinged design maximizes ventilation while the thermally broken aluminum frame delivers superior energy efficiency.

Slim 2-inch frames maximize natural light. Multi-point espagnolette locking, EPDM gaskets, and 24mm Low-E argon-filled IGUs meet or exceed ENERGY STAR for all Texas climate zones.

SAVE 30–50% vs. comparable US & European manufactured products — same quality, direct from factory

KEY FEATURES

- Outward-opening side-hinged operation
- Thermally broken aluminum with polyamide barrier
- Multi-point espagnolette locking with EPDM gaskets
- Optional retractable insect screen available
- AAMA 2604/2605 powder coat finish
- Custom sizes down to the millimeter

TECHNICAL SPECIFICATIONS

SPEC	DETAIL	SPEC	DETAIL
Frame Material	Thermally broken aluminum, polyamide barrier	**Finish**	Matte black powder coat, AAMA 2604/2605
Frame Profile	2” slim frames, mitered corners	**Gaskets**	EPDM dual weather stripping
Glass Unit	24mm double-pane IGU, Low-E, argon	**Sizes**	Custom sizes down to the millimeter
Operation	Side-hinged outward opening	**Energy**	ENERGY STAR, U-factor 0.30
Locking	Multi-point espagnolette	**Warranty**	10-year frame, 2-year hardware

ENERGY PERFORMANCE RATINGS

0.30	0.23	0.49	53
U-Factor	Solar Heat Gain Coefficient	Visible Transmittance	Condensation Resistance