

## DOUBLE ENTRY DOOR

### *Grand Entrance. Symmetrical Double Panel.*



A wide double-panel in-swing entry door built on a 2.0mm 6063-T5 thermal-break aluminum profile. Each panel features 6mm + 20A + 6mm double tempered Low-E glass with argon fill and a black silicone spacer for premium thermal and acoustic performance.

All hardware included on both panels — CMECH handles, multi-point locking, matching black trim. Optional SDL grid for traditional architecture. Matte black powder coat finish standard.

**SAVE 30–50%** vs. comparable US & European manufactured products — same quality, direct from factory

#### KEY FEATURES

- 2.0mm gauge 6063-T5 thermal-break aluminum frame
- 6mm + 20A + 6mm double tempered Low-E glass per panel
- Black silicone spacer, double silver Low-E coating
- CMECH handles and multi-point locking on both panels
- Matte black powder coat finish
- Symmetrical in-swing standard, custom configurations available

#### TECHNICAL SPECIFICATIONS

SPEC	DETAIL	SPEC	DETAIL
Frame	2.0mm 6063-T5 aluminum, thermal break	Finish	Matte black powder coat
Glass Unit	6mm + 20A + 6mm double tempered	Glass Type	Low-E with double silver coating
Spacer	Black silicone warm-edge spacer	Fill	Argon gas for noise reduction
Hardware	CMECH handles, both panels	Grid Option	SDL (simulated divided light)
Operation	Symmetrical in-swing, high track	Sizes	Custom sizes down to the millimeter

#### GLASS & FRAME HIGHLIGHTS

**6063-T5**

Aluminum Alloy

**Low-E**

Double Silver Coating

**Argon**

Gas-Filled IGU

**CMECH**

Handles & Locks