

FIXED WINDOW

Maximum Light. Zero Compromise.



Unobstructed views and maximum natural light through a non-operable, permanently sealed frame. With no moving parts, it offers the highest thermal and acoustic performance in our window lineup — ideal for picture windows, transoms, and architectural accent glazing.

Ultra-slim 2-inch frames virtually disappear, letting the glass take center stage. Structural silicone glazing and precision-mitered corners create a clean, modern aesthetic.

SAVE 30–50% vs. comparable US & European manufactured products — same quality, direct from factory

KEY FEATURES

- Non-operable sealed unit for maximum performance
- Thermally broken aluminum with polyamide barrier
- Structural silicone glazing for clean sightlines
- 24mm Low-E argon insulated glass units
- AAMA 2604/2605 powder coat finish
- Custom sizes down to the millimeter

TECHNICAL SPECIFICATIONS

SPEC	DETAIL	SPEC	DETAIL
Frame Material	Thermally broken aluminum, polyamide barrier	Finish	Matte black powder coat, AAMA 2604/2605
Frame Profile	2" slim frames, mitered corners	Gaskets	EPDM full perimeter seal
Glass Unit	24mm double-pane IGU, Low-E, argon	Sizes	Custom sizes down to the millimeter
Operation	Non-operable, fixed unit	Energy	ENERGY STAR, U-factor 0.28
Glazing	Structural silicone, clean exterior	Warranty	10-year frame, 10-year sealed unit

ENERGY PERFORMANCE RATINGS

0.28

U-Factor

0.22

Solar Heat Gain
Coefficient

0.49

Visible
Transmittance

55

Condensation
Resistance