

SINGLE HUNG WINDOW

Classic Style. Modern Performance.



Pairs a traditional vertical sliding design with advanced European thermal technology. The lower sash slides vertically while the upper sash remains fixed, delivering reliable ventilation with a timeless aesthetic that suits any architectural style.

Clean 2-inch frames and a tilt-in lower sash make cleaning easy, even on upper floors. Spring-loaded balances ensure smooth, effortless operation for years.

SAVE 30–50% vs. comparable US & European manufactured products — same quality, direct from factory

KEY FEATURES

- Vertical sliding lower sash with tilt-in cleaning
- Thermally broken aluminum with polyamide barrier
- Spring-loaded balance system for smooth operation
- Insect screen included
- AAMA 2604/2605 powder coat finish
- Custom sizes down to the millimeter

TECHNICAL SPECIFICATIONS

SPEC	DETAIL	SPEC	DETAIL
Frame Material	Thermally broken aluminum, polyamide barrier	Finish	Matte black powder coat, AAMA 2604/2605
Frame Profile	2" slim frames, mitered corners	Gaskets	EPDM dual weather stripping
Glass Unit	24mm double-pane IGU, Low-E, argon	Sizes	Custom sizes down to the millimeter
Operation	Vertical sliding, tilt-in cleaning	Glazing	T-30 Low-E · 6+12 Argon+6 (24mm)
Locking	Cam-action sash lock, black finish	Warranty	10-year frame, 2-year hardware

ENERGY PERFORMANCE — STANDARD 60 mm

0.37

U-Factor

0.17

SHGC