

## SLIDING DOOR

*Smooth Glide. Wide Opening.*



Effortless operation on precision stainless steel rollers, opening wide to connect indoor and outdoor living. Thermally broken aluminum frames match the energy performance of our window line.

Slim 2-inch frames maximize glass area for panoramic views. The multi-track system supports 2 to 4 panel configurations, with lift-and-slide operation for an airtight seal closed and fingertip-light gliding open.

**SAVE 30–50%** vs. comparable US & European manufactured products — same quality, direct from factory

### KEY FEATURES

- Lift-and-slide operation on stainless steel rollers
- Thermally broken aluminum with polyamide barrier
- Multi-track system supports 2 to 4 panel configurations
- Optional retractable insect screen available
- AAMA 2604/2605 powder coat finish
- Custom sizes down to the millimeter

### TECHNICAL SPECIFICATIONS

SPEC	DETAIL	SPEC	DETAIL
<b>Frame Material</b>	Thermally broken aluminum, polyamide barrier	<b>Finish</b>	Matte black powder coat, AAMA 2604/2605
<b>Frame Profile</b>	2" slim frames, flush interior track	<b>Gaskets</b>	EPDM dual weather stripping
<b>Glass Unit</b>	24mm double-pane IGU, Low-E, argon	<b>Sizes</b>	Custom sizes down to the millimeter
<b>Operation</b>	Lift-and-slide, steel rollers	<b>Energy</b>	ENERGY STAR, U-factor 0.30
<b>Configuration</b>	2, 3, or 4 panel layouts	<b>Warranty</b>	10-year frame, 2-year hardware

### ENERGY PERFORMANCE RATINGS

**0.30**

U-Factor

**0.23**

Solar Heat Gain  
Coefficient

**0.49**

Visible  
Transmittance

**53**

Condensation  
Resistance