

# SLIDING WINDOW

*Smooth Operation. Modern Design.*



Glides effortlessly on precision stainless steel rollers, offering easy operation and excellent ventilation. The thermally broken aluminum frame provides superior energy efficiency while the slim profile maximizes your view.

Clean 2-inch frames and a flush interior track create a modern, streamlined look. Interlock seals and compression gaskets deliver outstanding weather resistance.

**SAVE 30–50%** vs. comparable US & European manufactured products — same quality, direct from factory

## KEY FEATURES

- Horizontal sliding on stainless steel rollers
- Thermally broken aluminum with polyamide barrier
- Interlock meeting rail with compression seals
- Optional retractable insect screen available
- AAMA 2604/2605 powder coat finish
- Custom sizes down to the millimeter

## TECHNICAL SPECIFICATIONS

SPEC	DETAIL	SPEC	DETAIL
<b>Frame Material</b>	Thermally broken aluminum, polyamide barrier	<b>Finish</b>	Matte black powder coat, AAMA 2604/2605
<b>Frame Profile</b>	2" slim frames, flush interior track	<b>Gaskets</b>	EPDM, interlock meeting rail
<b>Glass Unit</b>	24mm double-pane IGU, Low-E, argon	<b>Sizes</b>	Custom sizes down to the millimeter
<b>Operation</b>	Horizontal sliding, steel rollers	<b>Energy</b>	ENERGY STAR, U-factor 0.30
<b>Locking</b>	Cam-action crescent lock	<b>Warranty</b>	10-year frame, 2-year hardware

## ENERGY PERFORMANCE RATINGS

**0.30**

U-Factor

**0.23**

Solar Heat Gain  
Coefficient

**0.49**

Visible  
Transmittance

**53**

Condensation  
Resistance